



TRAPS.CO.NZ

www.traps.co.nz info@traps.co.nz

BT200 TRAP and BOX

INSTRUCTIONS TO SET THE TRAP

1. To set the trap, first open the tamperproof lid. Using a Phillips screwdriver, undo the securing screw by turning in an anticlockwise direction. (Fig 1)



Figure 1

2. Swing open the lid horizontally, using the nail as a pivot.

3. Place the lure/bait in the depression/hole to the side of the trigger plate. We recommend Traps.co.nz [Rat Lure or Mustelid Lure](#) for stoats and ferrets.



Figure 2



Figure 3

4. Using gloved hands, pull the wire handle upwards until the kill bar catches lightly behind the top lip of the trigger arm, and is sitting over the hinge of the trigger arm. The bottom tapered tip of the trigger arm should be resting against the indented square area on the stem of the trigger plate that acts as a “stop”. See Fig 4.



Figure 4



Figure 5

IMPORTANT: Secure the top of the kill bar with the safety catch provided (See Figures 5 and 6) while you use your other hand to stabilize the swinging trigger arm or adjust the positioning of the trigger plate to achieve the correct set against the “stop”.



Figure 6

5. Once set, carefully REMOVE THE SAFETY CATCH then swing the lid back into position and screw securely in place.
 6. Place the trap in an area where there is evidence of rodents or mustelids.
 7. Check the trap regularly – clean, rebait, and reset.
- See also [this link](#) for a helpful demonstration of the very similar DOC200.